

AvaSpec-HERO SensLine

The AvaSpec-HERO is the top of the line spectrometer!
Based on our High Sensitivity Compact (HSC) optical bench (f=100mm; NA=0.13) and a 1024x58 backthinned CCD detector, it offers the best of both worlds: high sensitivity and resolution!

The instrument is equipped with thermo-electric cooling, enabling long integration times in low light applications. In conjunction with our AS7010 electronics, including a high-end AD converter, noise is kept to a minimum, which offers you an excellent Signal to Noise and Dynamic Range performance.

A selection of gratings and slits offers you the flexibility of configuring the instrument for a wide range of applications in the 200-1160 nm range.

From low light fluorescence applications to demanding Raman applications, the AvaSpec-HERO is your ideal companion.

With the high-speed USB3.0 and Gigabit Ethernet communication interface, the connection to your computer is fast and simple.

Of course the digital IO ports enabling external triggering, control of shutters, and pulsed light sources from the Avantes line of instruments are available as well.

The Avaspec-HERO is standard equipped for use with replaceable slits, offering optimal flexibility for a variety of applications. The combination of all the above makes the AvaSpec-HERO your ideal companion for all your spectroscopic measurements.

AvaSpec-HERO



Technical Data

Optical Bench	HSC Symmetrical Czerny-Turner, 100 mm focal length, NA: 0.13
Wavelength range	200-1160 nm
Resolution	0.2-7 nm, depending on configuration (see table)
Stray-light	0.5%, depending on the grating
Sensitivity	445,000 counts/μW per ms integration time
Detector	CCD array image sensor with one stage TE Cooled, 1024 pixels
Temperature cooled CCD	Max. ΔT = 30 °C versus ambient
Signal/Noise	1200:1
Dynamic Range	40.000
AD converter	16-bit, 250 kHz
Integration time	5.2 ms- 60 sec
Interface	USB 3.0 high-speed, 5 Gbps Gigabit Ethernet 1 Gbps
Digital IO	HD-26 connector, 2 Analog in, 2 Analog out, 3 Digital bidirectional, trigger, sync., strobe, laser.
Sample speed with on-board averaging	5.2 ms/scan
Data transfer speed	5.2 ms/scan (USB3 and ETH)
Power supply	12VDC, 1.5A
Dimensions, weight	185 x 161 x 185mm, 3500 grams

The new AvaSpec-HERO is the answer for those who are in need of high resolution and high sensitivity!

Grating Selection Table for AvaSpec-HSC1024x58TEC-EVO

Use	Useable range (nm)	Spectral range (nm)	Lines/mm	Blaze (nm)	Order code
UV/VIS/NIR	200-1160	770-760*	300	300	HSC0300-0.30
UV/VIS/NIR	250-1160	770-760*	300	420	HSC0300-0.42
VIS/NIR	250-1160	577-553	400	550	HSC0400-0.55
UV/VIS	250-850	373-340*	600	400	HSC0600-0.40
VIS/NIR	250-1160	373-340*	600	650	HSC0600-0.65
VIS/NIR	500-1160	268-220*	830	900	HSC0830-0.90
UV/VIS	200-1160	182-130*	1200	400	HSC1200-0.40
VIS/NIR	500-1050	182-130*	1200	750	HSC1200-0.75
UV/VIS	200-580	84-61*	2400	270	HSC2400-0.27

* depends on the starting wavelength of the grating; the higher the wavelength, the bigger the dispersion and the smaller the range to select.

Resolution Table (FWHM in nm) for AvaSpec-HSC1024x58TEC-EVO

Grating (lines/mm)	Slit size (μm)					
	10	25	50	100	200	500
300	1.70	1.80	2.30	3.40	6.50	14.0
400	1.30	1.45	1.60	2.60	5.10	12.0
600	0.75	0.85	1.10	1.70	3.40	7.50
830	0.50	0.60	0.70	1.25	2.30	5.00
1200	0.32	0.40	0.48	0.80	1.45	3.50
2400	0.17	0.30	0.36	0.50	0.80	1.75

* Above values are average values. Due to optical properties resolution will be better in the lower wavelengths than in the higher wavelength range.

Ordering Information

AvaSpec-HSC1024x58TEC-EVO

- AvaSpec-HERO; High sensitivity fiber optic spectrometer, HSC 100mm bench design, 1024x58 pixel back illum TE cooled CCD detector, high-speed USB 3.0 and ETH interface, including AvaSoft-Basic, USB interface cable, specify grating, wavelength range and options

Options

SLIT-XX-RS	• Replaceable slit with SMA connector, specify slit size XX=10, 25, 50, 100, 200 or 500 μm.
SLIT-XX-RS-FCPC	• As SLIT-XX-RS, but with FC/PC connector
SLITKIT-SMA	• Slit kit containing 25, 50, 100, 200 or 500 μm slits, and the tools to replace the slit. SMA-connectors
SLITKIT-FCPC	• As SLITKIT-SMA, but with FC/PC connectors
OSF-YYY-3	• Order sorting filter for reduction of 2nd order effects, 3 mm thick, please specify YYY= 305, 395, 475, 515, 550, 600 nm
OSC-HSC300	• Order sorting coating for use with grating HSC0300-xx
OSC-HSC600	• Order sorting coating for use with grating HSC0600-xx and HSC0400-xx