

EVO Series, with 4k CMOS detector: StarLine AvaSpec-ULS4096CL-EVO

Another new member in our EVO series: the AvaSpec-ULS4096CL-EVO. Using CMOS technology instead of the conventional CCD technology, this spectrometer offers you the latest technology; ready for the next decade. The dominant position of CCD detectors in the spectrometer field is fading and new technologies like CMOS have evolved and become a suitable alternative. The AvaSpec-ULS4096CL-EVO offers you this latest technology ensuring a spectrometer platform for the coming years. In combination with our latest AS-7010 electronics it offers you a versatile device including USB3.0 Communication with 10x higher speed compared to USB2, and a second communication port which offers Gigabit Ethernet for integration in your company network and possibility for long distance communication at an affordable price.

Besides the high speed communication options, the EVO also offers a fast microprocessor and 50x more memory which can help you to store more spectra onboard and realise more functionality.

Options include a detector collection lens to enhance sensitivity in the 200-1100 nm range and order-sorting filter to reduce 2nd order effects. Furthermore, the AvaSpec-4096CL is available with a wide range of slit sizes, gratings and fiber-optic entrance connectors.

It comes complete with AvaSoft-Basic software, USB cable and an extensive manual.

The AvaSpec-ULS4096CL-EVO is also available as OEM unit, Bench only or Rackmount version.

With the 4096 pixels these spectrometers are tailored for high resolution applications like Plasma and LIBS.

AvaSpec-ULS4096CL



Technical Data

Optical Bench	ULS Symmetrical Czerny-Turner, 75 mm focal length
Wavelength range	200-1100 nm
Resolution	0.05 -20 nm, depending on configuration (see table)
Stray-light	0.19-1.0%, depending on the grating
Sensitivity	218.000 counts/ μ W per ms integration time
Detector	CMOS linear Image Sensor
Signal/Noise	335:1
AD converter	16-bit, 6 MHz
Integration time	9 μ s - 40s
Interface	USB 3.0 high-speed, 5 Gbps Gigabit Ethernet 1 Gbps
Sample speed with on-board averaging	0.70 ms /scan
Data transfer speed	0.70 ms/scan (USB3), 1.31 ms (ETH)
Digital IO	HD-26 connector, 2 Analog in, 2 Analog out, 13 Digital bidirectional, trigger, sync., strobe, laser
Power supply	Default USB3 power, 532 mA Or 12VDC, 300 mA
Dimensions, weight	177 x 127 x 44,5 mm (1 channel), 1155 grams

EVolutionary spectroscopy:

- Speed
- Network integration
- Multi-channel benefits

Grating Selection Table for AvaSpec-ULS4096CL-EVO

Use	Usable range (nm)	Spectral range (nm)	Lines/mm	Blaze (nm)	Order code
UV/VIS/NIR	200-1100**	891**	300	300	UA
UV/VIS/NIR	200-1100**	891**	300	300/1000	UNA-DB
UV-VIS	200-850	515	600	300	UB
UV	200-750	247-218*	1200	250	UC
UV	200-650	163-143*	1800	UV	UD
UV	200-580	113-69*	2400	UV	UE
UV	200-400	69-45*	3600	UV	UF
UV/VIS	250-850	515	600	400	BB
VIS/NIR	300-1100**	792**	300	500	VA
VIS	360-1000	495	600	500	VB
VIS	300-800	247-218*	1200	500	VC
VIS	350-750	142-89*	1800	500	VD
VIS	350-640	74-49*	2400	VIS	VE
NIR	500-1050	495	600	750	NB
NIR	500-1050	218-148*	1200	750	NC
NIR	600-1100	346-297	830	800	SI
NIR	600-1100**	495**	300	1000	IA
NIR	600-1100	495	600	1000	IB

* depends on the starting wavelength of the grating; the higher the wavelength, the bigger the dispersion and the smaller the range to select.

** please note that not all 4096 pixels will be used for the useable range

Resolution Table (FWHM in nm) for AvaSpec-ULS4096CL-EVO

Grating (lines/mm)	Slit size (μm)					
	10	25	50	100	200	500
300	0.50-0.70	1.20-1.30*	2.17	4.6	9.00	20.0
600	0.30-0.36*	0.58-0.60	1.17	2.20	4.5	10.0
830	0.25	0.48	0.93	1.7	3.4	8.0
1200	0.14-0.18*	0.30	0.62	1.08	2.2	5.0
1800	0.09-0.11*	0.18	0.36-0.40*	0.78	1.5	3.7
2400	0.07-0.09*	0.13-0.15*	0.26-0.32*	0.40-0.64*	1.1	2.7
3600	0.05-0.06*	0.10	0.19	0.4	0.8	2.0

* depends on the starting wavelength of the grating; the higher the wavelength, the bigger the dispersion and the better the resolution

**expected resolution gain with a 5 micrometer slit will be a factor 0.8

Ordering Information

AvaSpec-ULS4096CL-EVO

- Fiber-optic Spectrometer, 75 mm AvaBench, 4096 pixel CMOS detector 7 x 200 μm, USB powered, high-speed USB 3.0 and ETH interface, incl. AvaSoft-Basic, USB interface cable.
Specify grating, wavelength range and options.

PS-12V/1.0A

- External power supply, needed for operation in ETH mode or with USB2 ports.

Options

-RS	• Replaceable slit
DCL-UV/VIS-200	• Quartz Detector Collection Lens (200-1100 nm)
SLIT-XX	• Slit size, please specify XX = 5, 10, 25, 50, 100, 200 or 500 μm
SLIT-XX-RS	• Replaceable slit with SMA connector , specify slit size XX=25, 50, 100 or 200 μm . Only in combination with AvaSpec-ULS4096CL-EVO-RS
SLIT-XX-RS-FCPC	• as SLIT-XX-RS, but with FC/PC connector
OSF-YYY	• Order-sorting filter for reduction of 2nd order effects please specify YYY= 305, 395, 475, 515, 550 or 600 nm
OSC	• Order-sorting coating with 600 nm long-pass filter for BB (>350 nm) and VB gratings, recommended with OSF-305
OSC-UA	• Order-sorting coating with Linear Variable Filter for UA, VA gratings
OSC-UB	• Order-sorting coating with 350 and 600 nm long-pass filter for UB or BB (<350 nm) gratings
-FCPC	• FC/PC fiber-optic connector



www.phototechnica.co.jp

フォトテクニカ株式会社

〒336-0017 埼玉県さいたま市南区南浦和 1-2-17

TEL:048-871-0067 FAX:048-871-0068

e-mail: voc@phototechnica.co.jp

Using **CMOS technology** instead of conventional CCD technology, this spectrometer offers you the latest technology, ready for the next decade!