

Optical Chopper

C
9
9
5

Features:

- Wide Frequency Range 4 Hz to 5000 Hz
- Rock Solid Crystal Controlled Frequency
- Large 5 Digit LED Display
- Frequency resolution of 0.001 Hz
- External Clock Synchronization
- Covers 4 Hz to 5 KHz with only one blade
- Computer Interface for easy control
- Enclosed Chopper Blade



The C-995 is a microprocessor-based control system that utilizes direct-digital-synthesis to deliver precise optical chopping rates from 4 Hz to 5000 Hz. Equipped with a large five-digit LED readout, the C-995 controller enables digital entry of the desired chopping rates from the front panel. Additionally, the C-995 is equipped with a bi-directional Rs-232 port that permits the user to set the desired chopping rate to a resolution of .001 Hz and to read the status of the instrument.

The C-995, designed with a phase-locked-loop control system, allows the chopping rate to also be synchronized to a user-supplied external clock ranging from 4 Hz to 5 KHz. The controller is then used to measure and display the frequency of the external clock.

The C-995 chopping head is attached to the controller by means of a 10 foot coiled cord. The precision etched blade is fully enclosed for protection from inadvertent damage. (An optional exposed blade version is also available.)

There are two apertures and two sections (30 slots and 3 slots) for the high and low frequency ranges, respectively. The aperture diameter is 15 mm with a slot width of 4.5 mm (30 slot section) or 30 mm (3 slot section). The small 4.75 inch square outline and two inch maximum depth permits easy integration into compact optical setups. Dual #8-32 mounting holes permit the apertures to be placed at a height as low as 0.75 inches above an optical bench, or with the included 1/2 inch rod and stand, as high as 13 inches above the mounting surface.

The ease of use and convenience of this instrument are matched only by the high performance to price ratio that is typical of products from Terahertz Technologies Inc. The C-995 is backed by our standard two year warranty and our guarantee of customer satisfaction.

Terahertz
TTInc. Technologies




Made In the USA

**PHOTO
TECHNICA**

フォトテクニカ株式会社

〒336-0017 埼玉県さいたま市南区南浦和 1-2-17

TEL:048-871-0067 FAX:048-871-0068

e-mail: voc@phototechnica.co.jp

[http://: www.phototechnica.co.jp](http://www.phototechnica.co.jp)

© 03/2010 Terahertz Technologies Inc.

C-995 Optical Chopper Specifications

Chopping Frequency Range	4 Hz to 500 Hz (Inner slots), 40 Hz - 5 KHz (outer slots)
Aperture Size	0.6 inch diameter (15 mm), and 0.6 inch by 0.2 inch (15 x 4.5 mm)
Frequency Control	Phase-Locked-Loop, Direct Digital Synthesis
Frequency Uncertainty	±.0025 % of setting
Phase Jitter	0.1 % peak to peak, 3 slot section, 1.0 % peak to peak, 30 slot section
Settling Time to Phase Lock	< 3 seconds
External Clock Input Requirements	TTL, CMOS Compatible Square Wave, 4 Hz to 5000 Hz
Sync Signal Output	TTL, CMOS Compatible Square Wave
Display	Five Digit, high intensity green, 0.5 " high
Temp. Coefficient of Chopping Frequency	< 10 ppm/C
Frequency Resolution (W/Rs-232 Control)	.001 Hz
Frequency Resolution (W/Front Panel Control)	.01 Hz
Counter Resolution using External Clock	0.1 Hz, 1 Hz
Rs-232 Interface	9600 Baud, N-8-1, 3 wire
Chopper Head Mounting	Standard 8-32 tapped holes, mounting rod and stand is provided
Chopper Blade Diameter	4.1 inch diameter
Operating Temperature Range	0 - 40 C
Dimensions (Head)	4.5 " H x 4.5 " W x 2 " D, 114 mm x 114 mm x 51 mm
Dimensions (Controller)	2.7 " H x 7 " W x 9.1 " D, 69 mm, 178 mm, 231 mm
Interconnecting cable supplied	Coiled Cord 10 feet max length
Power Requirements	95-260 VAC, 50-60 Hz, 15 VA Max
CE Certification	Yes
Weight	3 lbs, 1.36 Kg
Accessories Provided	Mounting rod and stand, Rs-232 cable, Power Cord, Operating Manual
Standard Warranty	One year , Components
Application Software Provided	Downloadable from TTI website, www.terahertztechnologies.com

TTI reserves the right to change specifications without notice



Open Chopper



Enclosed Chopper

T

T

I

Terahertz
Technologies
nc.




Made In the USA

PHOTO
TECHNIC

フォトテクニカ株式会社

〒336-0017 埼玉県さいたま市南区南浦和1-2-17
TEL:048-871-0067 FAX:048-871-0068
E-mail: voc@photo Technica.co.jp
www.photo Technica.co.jp