

# NL300 SERIES



## BENEFITS

- ▶ High pulse energy (up to 1 J at 1064 nm, 450 mJ at 355 nm) ensures strong interaction with material which is excellent for LIBS and material ablation applications
- ▶ Cost-effective, single-cavity design with no amplifiers for easy alignment, high reliability and low maintenance costs
- ▶ Small size saves valuable space in the laboratory room
- ▶ Fast flashlamp replacement without realignment of laser cavity ensures easy maintenance
- ▶ Air cooling enables simple installation, easy operation and low maintenance costs
- ▶ Variety of interfaces: USB, RS232, optional LAN and WLAN ensures easy integration with other equipment

NL300 series electro-optically Q-switched nanosecond Nd:YAG lasers produce high energy pulses with 3–6 ns duration. Pulse repetition rate can be selected in range of 5–20 Hz. NL30×HT models are designed for maximum energy extraction from the active element. Up to 1000 mJ pulse energy can be produced at a 5 Hz pulse repetition rate.

A wide range of harmonic generator modules for generation up to a 5<sup>th</sup> harmonic is available. Harmonic generators can be combined with attenuators that allow smooth output energy adjustment without changing other laser parameters, i.e. pulse duration, pulse-to-pulse stability, divergence or beam profile. For a more detailed description of harmonic

and attenuator modules please check our harmonic generators selection guide on the page 64.

The extremely compact laser head is approximately 480 mm long and can be fitted into tight spaces. The laser power supply has a 330 × 490 mm footprint. Easy access to the water tank from the back side of the power supply facilitates laser maintenance. Replacement of flashlamp does not require removal of pump chamber from the laser cavity and does not lead to possible misalignment.

The powering unit can be configured with water-to-water or water-to-air heat exchangers. The latter option allows for laser operation without the use of tap water for cooling.

## Compact Flash-Lamp Pumped Q-switched Nd:YAG Lasers

### FEATURES

- ▶ Rugged sealed laser cavity
- ▶ Up to **1000 mJ** pulse energy
- ▶ Better than 1 % StDev pulse energy stability
- ▶ **5–20 Hz** pulse repetition rate
- ▶ **3–6 ns** pulse duration
- ▶ Thermo stabilized second, third, fourth and fifth harmonic generator modules
- ▶ Optional attenuators for fundamental and/or harmonic wavelengths
- ▶ Water-to-water or water-to-air cooling options
- ▶ Replacement of flashlamps without misalignment of laser cavity
- ▶ Remote control via keypad and/or RS232/USB port

### APPLICATIONS

- ▶ Material ablation
- ▶ LIBS (Light Induced Breakdown Spectroscopy)
- ▶ OPO pumping
- ▶ Remote Sensing
- ▶ LIDAR (Light Detection And Ranging)
- ▶ Mass Spectroscopy
- ▶ LIF (Light Induced Fluorescence)

For customer convenience the laser can be controlled via PS with LabView™ drivers (included) or a remote control pad. Both options allow easy control of laser settings.

SPECIFICATIONS <sup>1)</sup>

Model	NL303HT		NL305HT
Pulse repetition rate	10 Hz	20 Hz	10 Hz <sup>2)</sup>
Pulse energy:			
at 1064 nm	800 mJ	700 mJ	1000 mJ
at 532 nm <sup>3)</sup>	380 mJ	320 mJ	500 mJ
at 355 nm <sup>4)</sup>	250 mJ	210 mJ	320 mJ
at 266 nm <sup>5)</sup>	80 mJ	60 mJ	100 mJ
at 213 nm <sup>6)</sup>	13 mJ	10 mJ	20 mJ
Pulse energy stability (StdDev) <sup>7)</sup>			
at 1064 nm		1 %	
at 532 nm		1.5 %	
at 355 nm		3 %	
at 266 nm		3.5 %	
at 213 nm		6 %	
Power drift <sup>8)</sup>		±2 %	
Pulse duration <sup>9)</sup>		3–6 ns	
Polarization	vertical, >90 %		vertical, >65 %
Optical pulse jitter <sup>10)</sup>	<0.5 ns rms		
Linewidth	<1 cm <sup>-1</sup>		
Beam profile <sup>11)</sup>	Hat-Top in near and near Gaussian in far fields		
Typical beam diameter <sup>12)</sup>	~8 mm		~10 mm
Beam divergence <sup>13)</sup>	<0.6 mrad		
Beam pointing stability <sup>14)</sup>	50 μrad rms		
Beam height	68 mm		

PHYSICAL CHARACTERISTICS

Laser head size (W × L × H) <sup>15)</sup>	154 × 475 × 128 mm		
Power supply unit (W × L × H)	330 × 490 × 585 mm		
Umbilical length	2.5 m		

OPERATING REQUIREMENTS

Water consumption (max 20 °C) <sup>16)</sup>	<8 l/min	<12 l/min	<10 l/min
Ambient temperature	15–30 °C		
Relative humidity	20–80 % (non-condensing)		
Power requirements <sup>17) 18)</sup>	208–240 V AC, single phase 50/60 Hz		
Power consumption <sup>19)</sup>	<1 kVA	<1.5 kVA	<1.5 kVA
Cleanliness of the room	not worse than ISO Class 9		

<sup>1)</sup> Due to continuous improvement, all specifications are subject to change without notice. The parameters marked typical are not specifications. They are indications of typical performance and will vary with each unit we manufacture. Unless stated otherwise all specifications are measured at 1064 nm and for basic system without options.

<sup>2)</sup> Inquire for higher energy 5 Hz model.

<sup>3)</sup> With H300SH, H300S or H300SHC harmonic generator modules. See harmonic generator selection guide on the page 64 for more detailed information.

<sup>4)</sup> With H300THC harmonic generator modules. See harmonic generator selection guide on the page 64 for more detailed information.

<sup>5)</sup> With H300SH and H400FHC harmonic generator modules. See harmonic generator selection guide on the page 64 for more detailed information.

<sup>6)</sup> With H300FIHC harmonic generator module. See harmonic generator selection guide on the

page 64 for more detailed information.

<sup>7)</sup> Averaged from pulses, emitted during 30 sec time interval.

<sup>8)</sup> Measured over 8 hours period after 20 min warm-up when ambient temperature variation is less than ± 2 °C and humidity < ± 5%.

<sup>9)</sup> FWHM.

<sup>10)</sup> Relative to SYNC OUT pulse.

<sup>11)</sup> Near field (at the output aperture) TOP HAT fit is >70%.

<sup>12)</sup> Beam diameter is measured at 1064 nm at the 1/e<sup>2</sup> level.

<sup>13)</sup> Full angle measured at the 1/e<sup>2</sup> level.

<sup>14)</sup> Beam pointing stability is evaluated as movement of the beam centroid in the focal plane of a focusing element.

<sup>15)</sup> See harmonic generator selection guide on the page 64 for harmonic generators units sizes.

<sup>16)</sup> For water cooled version. Air cooled version does not require tap water for cooling.

<sup>17)</sup> Power requirements should be specified when ordering.

<sup>18)</sup> 110 V AC powering is available, please inquiry for details.

<sup>19)</sup> Required current rating can be calculated by dividing power value by mains voltage value.

