

# BiBurst

## Tunable GHz and MHz Burst with Burst-in-Burst Capability

Water-cooled **CARBIDE** and **PHAROS** lasers feature the tunable GHz and MHz burst option with burst-in-burst capability, known as BiBurst.

In standard mode, the laser emits a single pulse at a fixed frequency. In burst mode, the output consists of pulse packets instead of single pulses. Each packet consists of a specific number of equally separated pulses. MHz-Burst contains N pulses with a nanosecond period, while GHz-Burst contains P pulses with a picosecond period. When both burst modes are combined, the equally separated pulse packets contain sub-packets of pulses, forming the burst-in-burst or BiBurst.

**CARBIDE** and **PHAROS** lasers, equipped with tunable GHz and MHz bursts and BiBurst options, bring new capabilities to high-tech

manufacturing industries, such as consumer electronics, integrated photonic chip production, advanced display manufacturing, and quantum technologies.

Applications:

- Brittle material drilling and cutting
- Deep engraving
- Selective ablation
- Volume modification of transparent materials
- Hidden marking
- Surface polishing
- Functional surface structuring

### Specifications

Model		CARBIDE-CB3	PHAROS
GHz Burst	Intra burst pulse period <sup>1)</sup>	440 ± 40 ps	200 ± 40 ps
	Number of pulses, P <sup>2)</sup>	1 – 10 (up to 400) <sup>3)</sup>	1 – 25
MHz Burst	Intra burst pulse period	≈ 15 ns	
	Number of pulses, N <sup>2)</sup>	1 – 10	1 – 9 (7 with FEC) <sup>4)</sup>

<sup>1)</sup> Custom spacing is available on request. For CARBIDE-CB3-10MHz model standard pulse period is 1500 ps.

<sup>2)</sup> The maximum number of pulses in a burst depends on the laser repetition rate and energy. CARBIDE-CB3-10MHz model is limited up to 5 pulses.

<sup>3)</sup> The maximum number of P pulses can be increased to 350 – 400 with optional long GHz burst mode.

<sup>4)</sup> Fast energy control option. Enables formation of any pulse envelope at laser pulse repetition rate.

