

# P-LINK

1 and 4 channels, PC-based power monitors




## KEY FEATURES


- > **READS ALL POWER DETECTORS TYPES**  
Thermopiles and photodetectors of the PH Series
- > **PC-BASED**  
Connects to your PC with included software
- > **MULTI-CHANNEL CAPABILITIES**  
Available with 1 or 4 channels
- > **SERIAL COMMANDS**  
Serial commands are available on both versions to let you take full control
- > **REAL-TIME STATISTICAL FUNCTIONS**  
Max, min, average, standard deviation, RMS and PTP stability. Also high low alarm and post-analysis mode (P-LINK-4 only)
- > **USB, RS-232 OR ETHERNET**  
Choose your favourite communications port. The USB version is port-powered. Ethernet available only on 4-Channel version

## CONNECTIVITY


P-LINK (USB)



P-LINK (RS-232)



P-LINK-4



## ACCESSORIES



Additional 9V power supply  
(RS-232 version only)



USB & RS-232 cables



Pelican carrying case

# P-LINK

## Specifications



\*Also traceable to NRC-CNRC



	P-LINK (USB)	P-LINK (RS-232)	P-LINK-4
<b>DETECTOR TYPES</b>	Thermopiles, photodetectors	Thermopiles, photodetectors	Thermopiles, photodetectors
<b>CHANNELS/ DISPLAY</b>	1-Channel / PC-based	1-Channel / PC-based	4-Channels / PC-based
<b>POWER METER SPECIFICATIONS</b>			
Power range			
Thermopile	3 $\mu$ W to 0 kW	3 $\mu$ W to 0 kW	3 $\mu$ W to 30 kW
Photodetector	1 nW to 3 W	1 nW to 3 W	1 $\mu$ W to 3 W
Monitor accuracy	$\pm 0.5\%$ full scale	$\pm 0.5\%$ full scale	$\pm 0.5\%$ full scale
Statistics	• Current value, max, min, average, std dev, RMS & PTP stability, time	• Current value, max, min, average, std dev, RMS & PTP stability, time	• Current value, max, min, average, std dev, RMS & PTP stability, time
Response time	1 s	1 s	1 s
<b>DETECTOR COMPATIBILITY</b>			
Thermopile	Average power & single shot energy	Average power & single shot energy	Average power
Photodetector	Average power (mW, dBm)	Average power (mW, dBm)	Average power (mW)
<b>GENERAL SPECIFICATIONS</b>			
Number of channels	1	1	4
Digital display	Computer screen	Computer screen	Computer screen
Data display	<sup>1</sup> Real-time, histogram, statistics, Digital tuning needle	<sup>1</sup> Real-time, histogram, statistics, Digital tuning needle	<sup>1</sup> Real-time, graphic, statistics, high/low alarm, Post-analysis mode, multi-channel
Analog output	0 - 2 Volt, adjustable, full scale, $\pm 1\%$	0 - 2 Volt, adjustable, full scale, $\pm 1\%$	N/A
Serial commands and data transfer via	USB	USB	USB (standard) or ethernet (option)
Real-time data transfer rate	10 Hz	10 Hz	10 Hz
Dimensions	57W x 26H x 91D mm	57W x 26H x 91D mm	286W x 233H x 43D mm
Weight	0.12 kg	0.12 kg	2.5 kg
External power supply	100/240 VAC 50 - 60 Hz to 12 VDC 200 mA	100/240 VAC 50 - 60 Hz to 12 VDC 200 mA	100/240 VAC 50 - 60 Hz to 5 VDC, 3 A
<b>ORDERING INFORMATION</b>			
Product page			

a Using PC-Gentec-EO software.  
b Using Octolink software.

Specifications are subject to change without notice  
T 418.657.8003 I info@gentec-eo.com

**gentec-EO**

PRODUCT GUIDE 2022