

SUPER HP

Custom Sizes and Shapes, up to 100,000 W upon request



AVAILABLE MODELS (CUSTOM BUILT)



HP280/100A-10KW-HD
(10 kW-Water-Cooled)



HP210A-25KW-HD
(25 kW-Water-Cooled)



HP280-30KW-HD
(30 kW-Water-Cooled)

ACCESSORIES



Stand with Steel Post
For 25 kW Model



Extension Cables
(4, 15, 20 or 25 m)



5 m USB Cable
(Included)



Pelican Carrying Case

KEY FEATURES

1. **THE HIGHEST POWER HANDLING**
Custom models handle up to 100 000 W of continuous power
2. **STABLE READING**
Less sensitive to variations in water cooling temperature than any other high power water-cooled meter on the market
3. **INFINITE CUSTOMIZATION CAPABILITIES**
 1. Choose YOUR size
 2. Choose YOUR maximum power
 3. We will customize one just for you!
4. **COMPACT AND LIGHT WEIGHT**
Lighter and more compact than any other high power detector on the market, thanks to our unique design
5. **AVAILABLE WITH YAG AND CO₂ CALIBRATIONS**
All HP Models can be calibrated at YAG and CO₂ wavelengths with a calibration uncertainty of ±5%
6. **DIRECT USB CONNECTION TO A PC**
Each head comes with both a DB-15 connector (for use with a Gentec-EO monitor) and a USB2.0 output for direct connection to a PC. Other connectors available upon request
7. **TRACK WATER PARAMETERS**
Water flow and temperature are monitored in real time and displayed continuously

SEE ALSO

HOW IT WORKS	14
CALIBRATION	6
TECHNICAL DRAWINGS	110
COMPATIBLE MONITORS	
MAESTRO	20
TUNER	24
UNO	26
S-LINK	28
P-LINK	30
M-LINK	32
LIST OF ALL ACCESSORIES	196

APPLICATION NOTE

MEASURING IN VACUUM [202178](#)

Watch the Introduction video available on our website at www.gentec-eo.com

SUPER HP



*Also traceable to NRC-CNRC

SPECIFICATIONS

	HP280/100A-10KW-HD	HP210A-25KW-HD	NEW HP280A-30KW-HD	CUSTOMIZATION CAPABILITIES
MAX AVERAGE POWER	10 000 W	25 000 W	30 000 W	Up to 100 000 W
EFFECTIVE APERTURE	280 x 100 mm	210 x 210 mm	280 x 280 mm	Up to 400 x 400 mm
COOLING METHOD	Water-Cooled	Water-Cooled	Water-Cooled	Water-Cooled
MEASUREMENT CAPABILITY				
Spectral Range	0.19 – 20 μm	0.19 – 20 μm	0.19 - 20 μm	0.19 – 20 μm
Noise Equivalent Power ^a	±10 W	±20 W	±25 W	Adapted to Maximum Power
Minimum Average Power ^b	300 W	500 W	1 000 W	Adapted to Maximum Power
Rise Time (nominal)	20 sec	25 sec	25 sec	≤ 45 sec
Sensitivity (typ into 100 kΩ load)	0.2 mV/W	0.08 mV/W	0.07 mV/W	Adapted to Maximum Power
Calibration Uncertainty				
@ 1064 nm	±5 %			±5 %
@ 0.25- 2.5 μm	±6 %			±6 %
Repeatability	±2 %			±2 %
Linearity with Power	±2 %			±2 %
Linearity vs Beam Diameter ^c	±2 %			±2 %
DAMAGE THRESHOLDS				
Maximum Average Power Density ^d				
10 kW	3.5 kW/cm ²	3.5 kW/cm ²	3.5 kW/cm ²	3.5 kW/cm ²
25 kW	---	0.25 kW/cm ²	---	0.25 kW/cm ²
30 kW	---	---	0.2 kW/cm ²	0.2 kW/cm ²
PHYSICAL CHARACTERISTICS				
Effective Aperture	280 x 100 mm	210 x 210 mm	280 x 280 mm	Square Apertures Up to 400 x 400 mm Rectangular and Round Apertures also available
Absorber (High Damage Threshold)	HD			HD
Required Cooling Flow	(6 - 10) LPM <±1 LPM/min ^f	(12 - 15) LPM <±1 LPM/min ^f	0-30 kW: (15 - 18) LPM <±1 LPM/min ^f 0-10 kW: (8 - 12) LPM <±1 LPM/min ^f	Adapted to Maximum Power
Cooling Water				
Temperature Range	15 – 25 °C			15 – 25 °C
Rate of Temperature Change	< ±3°C/min			< ±3°C/min
Output Connectors	DB-15 cable & USB port			DB-15 cable & USB port
PCB Electrical Supply	Through USB or Gentec-EO Monitors			Through USB or Gentec-EO Monitors
Maximum Output Signal	2 V			Analog Output 2V or 12V
Dimensions	152H x 305W x 75D mm	229H x 229W x 80D mm	300H x 300W x 92D mm	
Weight (head only)	11 kg	16 kg	20 kg	
ORDERING INFORMATION				
Product Name	HP280/100A-10KW-HD	HP210A-25KW-HD	HP280A-30KW-HD	Please call for more information on our customization capabilities

Specifications are subject to change without notice

- a. Nominal value, actual value depends on electrical noise in the measurement system.
 b. For lower powers, call your Gentec-EO representative.
 c. For a centered beam with size from 20% to 80% of the total aperture.

- d. At 1064 nm, 1.07-1.08 μm and 10.6 μm.
 e. Average period > 1 min.
 f. > 1min



〒336-0017 埼玉県さいたま市南区南浦和 1-2-17
 TEL: 048-871-0067 FAX: 048-871-0068

<http://www.phototechnica.co.jp>
 e-mail: voc@phototechnica.co.jp