

UNO

Single Channel, Power Monitor



KEY FEATURES

1. **READS ALL POWER DETECTORS**
Thermopiles and photodetectors of the PH Series
2. **LARGE LCD DISPLAY**
 - 76 x 57 mm
 - 32 mm digits
3. **UNIQUE ERGONOMIC DESIGN**
Great for both handheld and tabletop use
4. **ACCURATE**
24 bit A/D converter for high resolution measurements
5. **SINGLE-BUTTON NAVIGATION**
Direct access and long press access to all the functions
6. **EXTREMELY LOW CONSUMPTION**
Lasts 670 hours with 4 AA alkaline batteries
7. **ECONOMICAL**
Get the best value for your money with this inexpensive and simple to use power monitor

NOW AVAILABLE

W/dBm

You can now toggle your display between Watts or dBm units

ACCESSORIES



Optional 9V Power Supply
(Model Number: 200960)



Wall Support
(Model Number: 201241)



Pelican Carrying Case

SEE ALSO

POWER DETECTORS	66
HIGH POWER SOLUTIONS	104
PHOTODETECTORS	118
THZ DETECTORS	134
OEM DETECTORS	150
LIST OF ALL ACCESSORIES	206

UNO



SPECIFICATIONS

UNO

DETECTOR TYPES	Thermopiles, Photodetectors (PH Series)
DISPLAY	LCD

POWER METER SPECIFICATIONS

Power Range	10 nW to 10 kW
Thermopile	Single Wide Range Scale
Photodetector	Autoscale
Digital Resolution	
PH Series	1 pW
XLP Series	1 μW
UP Series	1 mW
Monitor Accuracy	±1 %
Response Time	1 sec

DETECTOR COMPATIBILITY

Thermopiles	Average Power (W, dBm)
Photodetectors	Average Power (W, dBm)

GENERAL SPECIFICATIONS

Digital Display Size	76 x 57 mm LCD
Digit Height	32 mm
Digit Type	High Contrast Fields
Data Display	Real Time
Dimensions (Without Stand)	210W x 122H x 44D mm
Weight (With Batteries)	0.47 kg
Battery Type	4 x AA Alkaline
Battery Life (Estimated)	670 hours with detector
External Power Supply (Optional)	100/240 VAC 50-60 Hz to 9 VDC 1.66 A

ORDERING INFORMATION

Product Name	UNO
Product Number	200982

Specifications are subject to change without notice

フォトテクニカ株式会社	〒336-0017 埼玉県さいたま市南区南浦和 1-2-17	https://www.phototechnica.co.jp
	TEL:048-871-0067 FAX:048-871-0068	e-mail:voc@phototechnica.co.jp