

UNO

Single channel, power monitor



KEY FEATURES

- **READS ALL POWER DETECTORS**
Thermopiles and photodetectors of the PH Series
- **LARGE LCD DISPLAY**
 - 76 x 57 mm
 - 32 mm digits
- **UNIQUE ERGONOMIC DESIGN**
Great for both handheld and tabletop use
- **ACCURATE**
24 bit A/D converter for high resolution measurements
- **SINGLE-BUTTON NAVIGATION**
Direct access and long press access to all the functions
- **EXTREMELY LOW CONSUMPTION**
Lasts 670 hours with 4 AA alkaline batteries
- **ECONOMICAL**
Get the best value for your money with this inexpensive and simple to use power monitor

NOW AVAILABLE

W/dBm

You can toggle your display between Watts or dBm units

ACCESSORIES



Optional 9V power supply



Wall support



Pelican carrying case



UNO	
DETECTOR TYPES	Thermopiles, photodetectors (PH series)
DISPLAY	LCD
POWER METER SPECIFICATIONS	
Power range	10 nW to 10 kW
Thermopile	Single wide range scale
Photodetector	Autoscale
Digital resolution	
PH series	1 pW
XLP series	1 μW
UP series	1 mW
Monitor accuracy	±1%
Response time	1s
DETECTOR COMPATIBILITY	
Thermopiles	Average power (W, dBm)
Photodetectors	Average power (W, dBm)
GENERAL SPECIFICATIONS	
Digital display size	76x57mm LCD
Digit height	32mm
Digit type	High contrast fields
Data display	Real-time
Dimensions (without stand)	210W x 122H x 44D mm
Weight (with batteries)	0.47kg
Battery type	4 x AA alkaline
Battery life (estimated)	670 hours with detector
External power supply (optional)	100/240 VAC 50 - 60 Hz to 9 VDC 166 A
ORDERING INFORMATION	
Product page	