

AvaLight-HAL-S-MINI Tungsten-Halogen Light Source

AvaLight-HAL-S-MINI



From visible light to near infrared, that's where the AvaLight-HAL-S-Mini works best. It's a compact, stabilized halogen light source, with adjustable focusing of the fiber connection, maximizing output power at the desired wavelength. The light source also has adjustable output power to provide extra power or longer bulb life.

A filter-slot mounted on the front of the AvaLight-HAL-S-Mini accepts 1" round or 2" x 2" square filters, to block specific ranges of wavelengths or instantly lower the intensity.

The adjustable focus on the AvaLight-HAL-S-Mini helps you get the most out of your light source: it makes sure all possible power is transmitted through your optical fiber. Bulb replacement is easy and can be done in a matter of minutes.

Optionally a combined direct-attach cuvette holder and attenuator is available (CUV-ATT-DA-HAL). for attenuation you can use the Inline Filterholder, FH-INL, or the Inline attenuator, ATT-INL.

The optical output can be controlled through a dongle at the backside or from your spectrometer. At low setting the

lamp has a color temperature of 2700K but provides over 13000 hours of lifetime. The standard or medium setting changes the color temperature to 2850K and provides 50% more power with a bulb lifetime of 4000 hours. The high power setting gives a color temperature of 3000K, double power compared to the long-life setting and gives you up to 1000 hours of lifetime.

The AvaLight-HAL-S-Mini features an internal TTL-shutter, controllable from your AvaSpec spectrometer. This gives you the ability to use the auto-save dark option in AvaSoft spectroscopy software.




Figure 9 Spectral output of AvaLight-HAL-Mini

Technical Data

	AvaLight-HAL-S-Mini (standard)	AvaLight-HAL-S-Mini (long life)	AvaLight-HAL-S-Mini (high power)
Wavelength Range	360-2500 nm		
Stability	± 0.1%/ °C		
Time to stabilize	Ca. 10 min.		
Output to bulb	12.0 VDC/ 0.83A	11.3 VDC/ 0.8A	14.1 VDC/ 1.0A
Bulb Life	4000 hrs	> 13000 hrs	< 1000 hrs
Min. Optical power* 200 µm fiber	0.5 mWatt	0.35 mWatt	0.7 mWatt
Min. Optical power* 600 µm fiber	4.5 mWatt	3.2 mWatt	6 mWatt
Min. Optical power* 1000 µm fiber	10 mWatt	7 mWatt	14 mWatt
Bulb Color Temperature	2,850 K	2,730 K	3,000 K
Power requirement	12 VDC / 2.08A		
Temperature range	0-55 °C		
Dimensions, weight	150 x 78 x 37 mm, 510 grams		
Lifetime shutter	1,000,000 cycles (typical)		

* Optical power measured from 350-1100nm

Separate 50x50 mm filters to install in AvaLight-HAL-(S)-Mini

GL-WG305-3	Separate 50 x 50 x 3 mm long-pass filter > 305 nm
GL-KG3-3	Separate 50 x 50 x 3 mm band-pass filter, transparent > 325 nm and < 700 nm
GL-BG28-3	Separate 50 x 50 x 3 mm band-pass filter, transparent > 360 nm and < 500 nm
GL-GG385-3	Separate 50 x 50 x 3 mm long-pass filter > 385 nm
GL-GG475-3	Separate 50 x 50 x 3 mm long-pass filter > 475 nm
GL-OG515-3	Separate 50 x 50 x 3 mm long-pass filter > 515 nm
GL-OG550-3	Separate 50 x 50 x 3 mm long-pass filter > 550 nm
GL-NG9-1	Separate 50 x 50 x 1 mm Neutral Density filter (transmission 10%, 400-1100 nm)
GL-NG9-2	Separate 50 x 50 x 2 mm Neutral Density filter (transmission 1%, 400-1100 nm)
GL-NG9-3	Separate 50 x 50 x 3 mm Neutral Density filter (transmission 0.1%, 400-1100 nm)

More filter types available, please contact us for ordering information

Ordering Information

AvaLight-HAL-S-Mini	• 10W Tungsten Halogen lamp, fan cooled, incl. TTL shutter, needs extra PS-12V/2.08A power supply
AvaLight-HAL-S-RM	• Rack-mounted version of AvaLight-HAL-S-Mini
IC-DB26-2	• Interface cable AvaSpec-USB2/EVO platform to AvaLight-HAL-(S)-Mini for shutter and power setting
AvaLight-HAL-B-Mini	• 10W Tungsten Halogen Replacement bulb for AvaLight-HAL-(S)-Mini
PS-12V/2.08A	• Power supply 100-240VAC/12VDC, 2.08A, necessary for AvaLight-HAL-Mini
DONGLE-Mini-H	• Dongle for high power setting
DONGLE-Mini-L	• Dongle for long life setting



www.phototechnica.co.jp

フォトテクニカ株式会社

〒336-0017 埼玉県さいたま市南区南浦和 1-2-17

TEL:048-871-0067 FAX:048-871-0068

e-mail: voc@phototechnica.co.jp