Reflection Probes (Standard)



To obtain spectral information of the diffuse, or specular materials, reflection probes are used. The light from a light source is sent through six illumination fibers to the sample and the reflection is measured by a 7th fiber in the center of the reflection probe tip. The 7th fiber is coupled to a spectrometer configured to the appropriate wavelength range of interest. More illumination fibers can be added to get more energy from the light source and therefore increase the reflection signal level.

For measurements under an angle of 90°, the FCR-90-Option was developed. It's a special adapter with a mirror positioned at 45° and can be easily mounted on the tip of Avantes standard reflection probes.

The FCR-COL is an adjustable UV/ VIS/NIR collimating and focusing lens which enables focusing the measurement spot at an extended distance.

Technical Data

Fibers	7 fibers 200 mm or 400 mm core, 6 light-fibers, 1 read fiber, N.A.= 0.22. Standard 2 m length, splitting point in the middle.
Wavelength range	200-2500 nm (UV/VIS/NIR)
Connectors	SMA-905 connectors (2x)
Probe end	Stainless steel 316 cylinder, 50 mm long x 6.35 mm diameter. Optionally –PK for PEEK or –HY for Hastelloy® C276 (on request)
Jacketing	The optical fibers are protected by a silicon inner tube and a flexible stainless steel (BX, O.D. 6.0 mm) or chrome plated brass (ME, O.D. 5.0 mm) outer jacket. The jacketing also gives stress relieve.
Temperature	-30°C to 100°C. (-HT version 200 °C)
Pressure	Probe head 50 bar @ 25 °C
Bending	Minimum bend radius: Short term (few seconds) 20-40 mm, long term: 120 -240 mm



Ordering Information



www.phototechnica.co.jp フォトテクニカ株式会社

〒336-0017 埼玉県さいたま市南区南浦和 1-2-17 TEL:048-871-0067 FAX:048-871-0068 e-mail:voc@phototechnica.co.jp



Reflection Probes with multiple legs

For some measurements, a reflection probe is needed that can be coupled to two spectrometers and a light source. A good example is a reflection measurement in the UV/VIS and NIR range. For these situations, Avantes offers our reflection probes with multiple legs.

The light from a light source is coupled into a fiber bundle, consisting out of 17 illumination fibers which transport the light to the end of the probe. The reflected light is uniformly reflected into the two read fibers, each of which is connected to a spectrometer.

For measurements under a 90° angle, the FCR-90-Option has been developed. It is an adapter with a mirror mounted at 45° and can be easily mounted to the tip of these reflection probes. To accurately focus a small measurement spot from a higher distance, the FCR-COL adjustable US/VIS/NIR collimating/focusing lens is available and can be mounted to the tip of these probes.

Technical Data

Fibers	19 fibers 200 μm core, 17 light-fibers, 2 read fibers in 2 separate legs, N.A.= 0.22. Standard 2 m length, splitting point in the middle.
Wavelength range	200-2500 nm (UV/VIS/NIR)
Connectors	SMA-905 connectors (3x)
Probe end	Stainless steel 316 cylinder, 50 mm long x 6.35 mm diameter. Optionally –PK for PEEK or –HY for Hastelloy® C276 (on request)
Jacketing	The optical fibers are protected by a silicon inner tube and a flexible stainless steel (BX, O.D. 6.0 mm) or chrome plated brass (ME, 5.0 mm) outer jacket. The jacketing also gives stress relieve.
Temperature	-30°C to 100°C. (-HT version 200°C)
Pressure	Probe head 50 bar @ 25°C
Bending	Minimum bend radius: Short term (few seconds) 20 mm, long term: 120 mm



Ordering Information

FCR-19UVIR200-2-BX/ME*

FCR-90-Option

- Reflection probe UV/VIS/NIR, 17 x 200 μm UV/VIS/NIR illumination fibers, 2 read UV/VIS/NIR fibers in separate legs, 2 m length, 3 SMA term.
 90° Reflection add-on reflector for use with all ¼" reflection probes
- **FCR-COL** Adjustable UV/VIS/NIR Collimating/focusing lens FCR probes

* please specify jacket material

Options

-**HT** • High Temperature version (up to 200°C)



