# **Reflection Probe Holders**

#### **RPH-1 Reflection Probe Holder**

The RPH-1 is to be used with our standard reflection probes, which are 6.5 mm in diameter. The holder enables positioning of the probe tip in two angles: 45 degrees for diffuse reflection measurements and 90 degrees (normal to sample) for specular reflection. This assembly is mostly used to facilitate color measurements.

A setscrew is included to mount the probe into position. The RPH-1 is a small device, measuring only 60 by 30 by 30 millimeters. It's made of black anodized aluminum.



### **AFH-15 Angled Fiber Holder**

To do an angled measurement with a small 1.5 mm reflection probe or 1.5 mm stainless steel ferrule terminated fibers, the AFH-15 is the ideal accessory. Offering angles including 15°, 30°, 45°, 60°, 75° and 90°, reflection measurements with differing incident and collection angle can be easily

made with multiple, separate fibers for illumination and detection.

All 11 holes have a diameter of 1.6 mm and are equipped with a setscrew to mount the probes or fibers into position. The AFH-15 is made of black anodized aluminum.



# **AFH-Ocular**

Measurements on a small spot (less than 0.5 mm) can be challenging but the AFH-Ocular makes the job easier. The ocular enables visual location of the measurement spot on your sample. The holder is used in conjuction with our miniaturized reflection probe (FCR-7UV100-2-1x25) which has 7 x 100 µm fibers in a 6 around

1 configuration and the tip is 1 mm in diameter x 25 mm long.

Please note that a black cover over the ocular (not included) should be used during measuring to prevent ambient light from reaching the measurement spot.



## **Ordering Information**

RPH-1

• Reflection probe holder for 45/90 degree mounting of 6.5 mm reflection probes

AFH-15

 Angled fiber probe holder for measuring under different angles, needs 1.5 mm ferrule terminated fibers.

FC-UVIR200-2-1.5x40

• Fiber cable, 200 µm UVIR fiber, 2 m long, one end with SMA connector, other end with stainless steel ferrule, OD=1.5 mm x 40 mm length.

AFH-Ocular

• Angled fiber probe holder for precise measurements under 45 degrees incl. Ocular

FCR-7UVIR100-2-1x25

Reflection probe with 7x100 µm UVIR fibers to 1x25 mm stainless steel ferrule,
2 meter long with PVC/Kevlar protection sleeve and 2 SMA connectors



www.phototechnica.co.jp

# CA フォトテクニカ株式会社

〒336-0017 埼玉県さいたま市南区南浦和 1-2-17 TEL:048-871-0067 FAX:048-871-0068 e-mail:voc@phototechnica.co.jp

Three years limited warranty on all Avantes spectrometers, light sources and accessories

