

Reflection Probes with Small Tips

For some medical and semiconductor applications, a (very) small tip is desired to do reflectance measurements. Avantes offers two standard diameters of small tip reflection probes, 1.5 and 2.5 mm and each tip is normally 100 mm long.

The probe is configured with an illumination leg with six 200 μm fiber cables which connects to a fiber coupled light source

and a single 200 μm read fiber cable to measure the reflection via connection to a spectrometer.

A special angled fiber holder (AFH-15) is available for the 1.5 mm diameter reflection probe. This device enables reflection measurements under angles of 15, 30, 45, 60, 75 and 90 degrees. For more information, see 'Reflection probe holders'.



Technical Data

Fibers	7 fibers 200 μm core, 6 light-fibers, 1 read fiber, N.A.= 0,22. Standard 2 m length, splitting point in the middle.
Wavelength range	200-2500 nm (UV/VIS/NIR)
Connectors	SMA-905 connectors (2x)
Probe end	Stainless steel cylinder, 100 mm long x 1.5 or 2.5 mm diameter.
Jacketing	The optical fibers are protected by a Kevlar reinforced PTFE jacket with PVC sleeving. OD: 3.8 mm
Temperature	-20°C to 65°C
Bending	Minimum bend radius: Short term (few seconds) 20 mm, long term: 120 mm



Ordering Information

- FCR-7UVIR200-2-1.5x100** • Reflection probe, 1.5 mm tip, UV/VIS, 7 x 200 μm broadband fibers, 100 mm long, 2 m length, SMA
- FCR-7UVIR200-2-2.5x100** • Reflection probe, 2.5 mm tip, UV/VIS, 7 x 200 μm broadband fibers, 100 mm long, 2 m length, SMA

**PHOTO
TECHNICA**

www.phototechnica.co.jp

フォトテクニカ株式会社

〒336-0017 埼玉県さいたま市南区南浦和 1-2-17

TEL:048-871-0067 FAX:048-871-0068

e-mail: voc@phototechnica.co.jp

For diffuse or specular reflection measurements, take a look at the RPH-1 reflection probe holder