

NEW

EVO Series, with 4k CMOS detector: StarLine AvaSpec-ULS4096CL-EVO Spectrometer

EVO series: AvaSpec-ULS4096CL



Another new member in our new EVO series: the AvaSpec-ULS4096CL-EVO. Using CMOS technology instead of the conventional CCD technology, this spectrometer offers you the latest technology; ready for the next decade. The dominant position of CCD detectors in the spectrometer field is fading and new technologies like CMOS have evolved and become a suitable alternative. The AvaSpec-ULS4096CL-EVO offers you this latest technology ensuring a spectrometer platform for the coming years. In combination with our latest AS-7010 electronics it offers you a versatile device including USB3.0 Communication with 10x higher speed compared to USB2, and a second communication port which offers Gigabit Ethernet for integration in your company network and possibility for long distance communication at an affordable price.

Besides the high speed communication options, the EVO also offers a fast microprocessor and 50x more memory which can help you to store more spectra onboard and realise more functionality.

Options include a detector collection lens to enhance sensitivity in the 200-1100 nm range and order-sorting filter to reduce 2nd order effects. Furthermore, the AvaSpec-4096CL is available with a wide range of slit sizes, gratings and fiber-optic entrance connectors.

It comes complete with AvaSoft-Basic software, USB cable and an extensive manual.

The AvaSpec-ULS4096CL-EVO is also available as OEM unit, Bench only or Rackmount version.

With the 4096 pixels these spectrometers are tailored for high resolution applications like Plasma and LIBS.

Technical Data

Optical Bench	ULS Symmetrical Czerny-Turner, 75 mm focal length
Wavelength range	200-1100 nm
Resolution	0.05 –20 nm, depending on configuration (see table)
Stray-light	0.19-1.0%, depending on the grating
Sensitivity	218.000 counts/ μ W per ms integration time
Detector	CMOS linear Image Sensor
Signal/Noise	335:1
AD converter	16-bit, 6 MHz
Integration time	9 μ s – 40s
Interface	USB 3.0 high-speed, 5 Gbps Gigabit Ethernet 1 Gbps
Sample speed with on-board averaging	0.70 ms /scan
Data transfer speed	0.70 ms/scan (USB3), 1.31 ms (ETH)
Digital IO	HD-26 connector, 2 Analog in, 2 Analog out, 13 Digital bidirectional, trigger, sync., strobe, laser
Power supply	Default USB3 power, 532 mA Or 12VDC, 300 mA
Dimensions, weight	177 x 127 x 44,5 mm (1 channel), 1155 grams

EVOLutionary spectroscopy:

- SPEED
- NETWORK INTEGRATION
- MULTICHANNEL BENEFITS

Grating selection table for AvaSpec-ULS4096CL-EVO

Use	Lines/mm	Blaze (nm)	Order code
UV/VIS/NIR	300	300	UA
UV/VIS/NIR	300	300/1000	UNA-DB
UV/VIS	600	300	UB
UV	1200	250	UC
UV	1800	UV	UD
UV	2400	UV	UE
UV	3600	UV	UF
UV/VIS	600	400	BB
VIS/NIR	300	500	VA
VIS	TEST	500	VB
VIS	1200	500	VC
VIS	1800	500	VD
VIS	2400	VIS	VE
NIR	600	750	NB
NIR	1200	750	NC
NIR	830	800	SI
NIR	300	1000	IA
NIR	600	1000	IB

* depends on the starting wavelength of the grating; the higher the wavelength, the bigger the dispersion and the smaller the range to select.

** please note that not all 4096 pixels will be used for the useable range

Resolution table (FWHM in nm) for AvaSpec-ULS4096CL-EVO

Grating (lines/mm)	Slit size (μm)					
	10	25	50	100	200	500
300	0.50-0.70	1.20-1.30*	2.17	4.6	9.00	20.0
600	0.30-0.36*	0.58-0.60	1.17	2.20	4.5	10.0
830	0.25	0.48	0.93	1.7	3.4	8.0
1200	0.14-0.18*	0.30	0.62	1.08	2.2	5.0
1800	0.09-0.11*	0.18	0.36-0.40*	0.78	1.5	3.7
2400	0.07-0.09*	0.13-0.15*	0.26-0.32*	0.40-0.64*	1.1	2.7
3600	0.05-0.06*	0.10	0.19	0.4	0.8	2.0

* depends on the starting wavelength of the grating; the higher the wavelength, the bigger the dispersion and the better the resolution

Ordering Information

AvaSpec-ULS4096CL-EVO

PS-12V/1.0A

- Fiber-optic Spectrometer, 75 mm AvaBench, 4096 pixel CMOS detector 7 x 200 μm, USB powered, high-speed USB 3.0 and ETH interface, incl. AvaSoft-Basic, USB interface cable.
Specify grating, wavelength range and options.
- External power supply, needed for operation in ETH mode or with USB2 ports.

Using **CMOS technology** instead of conventional CCD technology, this spectrometer offers you the latest technology, ready for the next decade!