# **OPCPA** | HE

## **High-Energy OPCPA Systems**

#### **FEATURES**

- Multi-TW peak-power pulses at up to 1 kHz
- 800 nm, 1600 nm, or 2000 nm output
- Few-cycle pulse duration and high pre-pulse contrast
- Robust design with < 1-hour warm-up time
- Exceptional CEP and pulse energy stability
- Spectral-temporal pulse shaping options
- **Dual output option**



Applications like high-energy attosecond pulse generation, generation of high harmonics from solid targets, and laser electron acceleration all benefit from few-cycle pulse durations and excellent pulse contrast while requiring multi-millijoule pulse energy. Our most powerful high-energy OPCPA systems are scalable to multi-TW peak powers at kHz repetition rates while maintaining few-cycle pulse durations. Thus, they fit the

most demanding requirements while providing stability and reliability unprecedented for systems of this scale. Furthermore, > 10<sup>12</sup> pre-pulse contrast is obtained without complex and lossy nonlinear pulse cleaning techniques, while < 250 mrad CEP stability and < 1.5% pulse energy stability are maintained throughout a full day of operation, making it a robust and reliable multi-TW system.

#### **SPECIFICATIONS**


Model		ОРСРА-НЕ		
Center wavelength	800 nm	1600 nm	2000 nm	
Pump source	Picosecond Nd:YAG lasers, seeded by ORPHEUS-OPCPA			
Repetition rate	10 Hz – 1 kHz			
Maximum output pulse energy 1)	250 mJ	100 mJ	50 mJ	
Pulse duration 1)	< 9 fs	< 50 fs	< 30 fs	
CEP stability, 1h 1) 2)	< 250 mrad			
Long-term power stability, 8 h 1) 3)	< 1.5%			
Pulse-to-pulse energy stability, 1 min 1) 3)	<1.5%			

- 1) Typical values. For custom inquiries, contact sales@lightcon.com.
- <sup>2)</sup> CEP values calculated from unaveraged, single-shot measurements.
- 3) Expressed as as normalized root mean squared deviation (NRMSD).







#### Performance at 800 nm




High-dynamic-range third order autocorrelation measurement of an OPCPA-HE system






OPCPA-HE pulse energy, f-2f interferogram and CEP stability measured over 16 h




Temporal profile of OPCPA-HE output pulses measured with a self-referenced spectral interferometry device

### Performance at 2000 nm



Temporal profile of OPCPA-HE output pulses at 2  $\mu m$ 



Pulse-to-pulse energy stability of OPCPA-HE at 2  $\mu m$ 



〒336-0017 埼玉県さいたま市南区南浦和 1-2-17 TEL:048-871-0067 FAX:048-871-0068 e-mail:voc@phototechnica.co.jp

