

Beam delivery devices

4Lasers designs and manufactures compact laser beam delivery systems, laser beam expanders, reducers, divergence compensators and laser power attenuators, which are used to increase or decrease laser beam diameter, control beam divergence, and adjust laser power.



Compact motorized beam expanders MEX
 High-power motorized beam expanders MEX-HP
 Variable laser beam expanders, reducers VEX
 Fixed ratio laser beam expanders FEX
 Motorized laser power attenuators LPA
 Advanced motorized laser power attenuators LPA-A
 Manual laser power attenuators LPA-M
 Laser power attenuators LPA-OEM
 Flat top converter FTC
 Motorized polarization rotator MRO
 Manual 4 axis translation stage

www.phototechnica.co.jp
 〒336-0017 埼玉県さいたま市南区南浦和 1-2-17
 TEL:048-871-0067 FAX:048-871-0068
 e-mail: voc@phototechnica.co.jp

Compact motorized beam expanders MEX



Motorized laser beam expanders MEX series are used to increase the laser beam diameter and adjust divergence. Standard or custom-made beam expanders feature a unique mechanical closed loop sliding-lens design ensuring high pointing stability and minimal dimensions.

These variable magnification (zoom) beam expanders and reducers are designed for required wavelength and each type of our beam expanders has motorized divergence adjustability.

- Main features**
- Highest beam pointing stability (< 0.1 mrad)
 - All-in-one design with integrated controller
 - Two lens simultaneous movement assuring no misfocus
 - Absolute encoder (both lenses)
 - Adjustment time < 1s (all magnifications)
 - Fused silica optical elements
 - No homing after switching on/off
 - Diffraction limited performance for all magnifications

- Application examples**
- Precise laser micromachining
 - Life sciences
 - Research

Standard specifications

MOTORIZED BEAM EXPANDERS SPECIFICATIONS	
Adjustment	Motorized
Divergence	Adjustable
Clear input aperture	11.5 mm
Lens material	UVFS
Transmission	>97%
Controller	Integrated
Control interface	USB or RS232
Housing material	Black anodized aluminum
LIDT	3 J/cm ² (10 ns @ 355nm) 5 J/cm ² (10 ns @ 532 nm) 10 J/cm ² (10 ns @ 1064 nm)

*Custom design available

Standard products

ITEM MODEL	EXPANSION	CLEAR INPUT APERTURE	CLEAR OUTPUT APERTURE	RECOMMENDED MAX. INPUT BEAM SIZE, 1/1E	DIMENSIONS (H X W X L)	WAVELENGTH	POINTING STABILITY	SKU
MEX13	1.0x - 3.0x continuous	11.5 mm	23 mm	ø7 mm - 1x ø3 mm - 3x	45 x 45 x 140 mm	343-355 nm	< 0.2 mrad	4857
						343-355 nm	< 0.3 mrad	4858
						515-532 nm	< 0.2 mrad	4856
						515-532 nm	< 0.3 mrad	4859
						1030-1064 nm	< 0.2 mrad	4855
						1030-1064 nm	< 0.7 mrad	4855
						343-355 + 515-532 nm	< 0.2 mrad	4928
						343-355 + 515-532 nm	< 0.3 mrad	4131
						515-532 + 1030-1064 nm	< 0.3 mrad	4858
						515-532 + 1030-1064 nm	< 0.2 mrad	4927
MEX18	1.0x - 8.0x continuous	11.5 mm	38 mm	ø7 mm - 1x ø3 mm - 5x ø3 mm - 8x	45 x 45 x 237 mm	343-355 nm	< 0.3 mrad	4121
						515-532 nm	< 0.5 mrad	9226
						515-532 nm	< 0.3 mrad	4842
						1030-1064 nm	< 0.5 mrad	4841
						343-355 + 515-532 nm	< 0.3 mrad	4844
						515-532 + 1030-1064 nm	< 0.5 mrad	4843

Mounting options for motorized beam expanders MEX

MOUNTING OPTION	FOR BEAM HEIGHT OF	SKU
Manual 4 axis translation stage M2STAGE	27 mm (ø2 mm travel)	12571

www.phototechnica.co.jp
 〒336-0017 埼玉県さいたま市南区南浦和 1-2-17
 TEL:048-871-0067 FAX:048-871-0068
 e-mail: voc@phototechnica.co.jp

High-power motorized beam expanders MEX-HP



High power motorized laser beam expanders MEX series are used to increase the laser beam diameter and adjust divergence. The optical design is dedicated for high power ultraviolet femtosecond laser applications. These magnification (zoom) beam expanders are designed for required wavelength and each type of our beam

expanders has motorized divergence adjustability. Standard or custom-made beam expanders feature a unique mechanical closed loop sliding-lens design ensuring high pointing stability and minimal dimensions.

- Main features**
- High power optical design (up to 200 W @ 1030 nm, 500 fs, 1 Mhz)
 - No internal reflections on optical elements
 - Highest beam pointing stability < 0.2 mrad
 - All-in-one design with an integrated controller
 - Two lens simultaneous movement assuring no misfocus
 - Absolute encoder (both lenses)
 - Fused silica optical elements
 - Diffraction limited performance for all magnifications

- Application examples**
- Precise laser micromachining
 - High power laser beam management
 - Research

Standard specifications

HIGH POWER MOTORIZED LASER BEAM EXPANDERS SPECIFICATIONS	
Adjustment	Motorized
Divergence	Adjustable
Lens material	UVFS
Transmission	>97% (MEX13-HP), >95% (MEX15-HP)
Control interface	USB or RS232
Controller	Integrated
Housing material	Black anodized aluminum
Max. laser power	up to 200 W @ 1030 nm, 500 fs, 1 Mhz
LIDT	3 J/cm ² (10 ns @ 355nm) 5 J/cm ² (10 ns @ 532 nm) 10 J/cm ² (10 ns @ 1064 nm)

*Custom design available

Standard products

ITEM MODEL	EXPANSION	CLEAR INPUT APERTURE	CLEAR OUTPUT APERTURE	RECOMMENDED MAX. INPUT BEAM SIZE, 1/1E	DIMENSIONS (H X W X L)	WAVELENGTH	POINTING STABILITY	SKU
MEX13-HP	1.0x - 3.0x continuous	11.5 mm	28 mm	ø7 mm - 1x ø6 mm - 3x	60 x 60 x 207 mm	343-355 nm	< 0.5 mrad	9242
						343-355 nm	< 0.2 mrad	9243
						515-532 nm	< 0.5 mrad	9240
						515-532 nm	< 0.2 mrad	9241
						1030-1064 nm	< 0.5 mrad	9239
						1030-1064 nm	< 0.2 mrad	9244
						343-355 + 515-532 nm	< 0.2 mrad	9247
						343-355 + 515-532 nm	< 0.5 mrad	9246
						515-532 + 1030-1064 nm	< 0.5 mrad	9245
						515-532 + 1030-1064 nm	< 0.2 mrad	9248
MEX15-HP	1.0x - 5.0x continuous	11.5 mm	24 mm	ø7 mm - 1x ø3.3 mm - 5x	65 x 65 x 250 mm	343-355 nm	< 0.5 mrad	9250
						515-532 nm	< 0.5 mrad	9250
						1030-1064 nm	< 0.5 mrad	9248
						343-355 + 515-532 nm	< 0.5 mrad	9254

Mounting options for high-power motorized beam expanders MEX-HP

MOUNTING OPTION	FOR BEAM HEIGHT OF	SKU
Manual 4 axis translation stage M2STAGE-HP (Additional adapter included)	27 mm (ø2 mm travel)	12571

www.phototechnica.co.jp
 〒336-0017 埼玉県さいたま市南区南浦和 1-2-17
 TEL:048-871-0067 FAX:048-871-0068
 e-mail: voc@phototechnica.co.jp

4 LASERS

Variable beam expanders VEX and reducers VRE



4Lasers introduces variable manual beam expanders VEX series used to increase or decrease the laser beam diameter. Standard or custom-made laser beam expanders for the UV, visible, and NIR spectral ranges feature a unique mechanical sliding-lens design, ensuring a high pointing stability and minimal dimensions. These variable magnification (zoom) beam expanders are designed for the required wavelength and each type of our beam expanders have

divergence adjustability. All optical elements of beam expanders are made of fused silica with high LIDT coatings and provide stable and reliable performance even when using them with high power lasers. Large input and output apertures allow the optical beam expanders to produce diffraction limited expanded (or reduced) beams for a wide range of input beams.

Main features

- Highest beam pointing stability (< 0.5 mrad)
- Fused silica optical elements
- Grease free mechanical design
- Sliding lens design
- Diffraction limited performance for all magnifications

Application examples

- Laser micromachining
- Research

Standard specifications

VARIABLE BEAM EXPANDERS AND REDUCERS SPECIFICATIONS	
Adjustment	Manual
Divergence	Adjustable
Pointing stability	<0.5 mrad, <1 mrad (VEX13-HP)
Lens material	UVFS
Transmission	>97%, >95% (VEX15-HP)
LIDT	3 J/cm ² (10 ns @ 355nm)
	5 J/cm ² (10 ns @ 532 nm)
	10 J/cm ² (10 ns @ 1064 nm)

Standard products

ITEM MODEL	EXPANSION	CLEAR INPUT APERTURE	CLEAR OUTPUT APERTURE	RECOMMENDED MAX. INPUT BEAM SIZE, 1/e ²	DESIGN	DIMENSIONS	MOUNTING OPTIONS	WAVELENGTH	SKU
VEX13	1.0x - 2.0x continuous	11 mm	23.5 mm	ø7 mm - 1x ø5 mm - 3x	Standard	ø42 x 110 mm	M20x1 external, SM1 internal, ø38.1 mm (1.5"), T-mount (M42x0.75)	343-355 nm	4987
								515-532 nm	4987
								1030-1064 nm	4985
								343-355 + 515-532 nm	4991
								515-532 + 1030-1064 nm	4990
VEX18	1.0x - 8.0x continuous	11 mm	40 mm	ø7 mm - 1x ø5.3 mm - 3x ø3.2 mm - 8x	Standard	ø53 x 203 mm	SM2, ø50.8 mm (2")	343-355 nm	4495
								515-532 nm	4725
								1030-1064 nm	4992
								343-355 + 515-532 nm	4456
								515-532 - 1030-1064 nm	4994
VEX15-HP	1.0x - 5.0x continuous	11 mm	26 mm	ø7 mm - 1x ø5.3 mm - 3x	High power	ø69 x 255 mm	T-mount, SM2, ø50.8 mm (2")	515-532 + 1030-1064 nm	9273
								343-355 nm	4977
VRE13	0.33x - 1.0x continuous	22 mm	11 mm	ø15 mm - 0.33x ø7 mm - 1x	Standard	ø42 x 110 mm	M20x1 external, SM1 internal, ø38.1 mm (1.5"), T-mount (M42x0.75)	515-532 nm	4995
								343-355 + 515-532 nm	7809
								515-532 + 1030-1064 nm	4999

Mounting options for variable beam expanders VEX

MOUNTING OPTION	FOR BEAM HEIGHT OF	SKU
Fixed post mounting set	100-125 mm (4" - 5")	9336
Fixed post mounting set	76.2 mm (3")	9337
X-Y adjustable (3 adjusters) kinematic mount with post holder, D50, 8mm option	76.2 mm (3")	9346
X-Y adjustable (3 adjusters) kinematic mount with post holder, SM2 option	76.2 mm (3")	9347
X-Y adjustable (3 adjusters) kinematic mount with post holder, D50, 8mm option	100-125 mm (4" - 5")	9350
X-Y adjustable (3 adjusters) kinematic mount with post holder, SM2 option	100-125 mm (4" - 5")	9351



www.phototechnica.co.jp
フォトテクニカ株式会社

〒336-0017 埼玉県さいたま市南区南浦和 1-2-17
TEL: 048-871-0067 FAX: 048-871-0068
e-mail: voc@phototechnica.co.jp

4 LASERS

Fixed ratio beam expanders FEX



Fixed ratio beam expanders FEX series are used to increase the laser beam diameter. The FEX model diversity cover the UV, visible and NIR spectral ranges. These compact beam expanders are designed for required wavelength and have divergence adjustability.

All optical elements of beam expanders are made of fused silica with high LIDT coatings and provide a stable and reliable performance even using them with high power lasers.

Main features

- Divergence adjustment
- Galilean optical design
- UVFS optical elements
- UVFS optical elements
- Grease free mechanical design
- Wide wavelength adoption - 200 nm to 2 μm

Application examples

- Laser material processing
- Medical
- Research

Standard specifications

FIXED RATIO BEAM EXPANDER SPECIFICATIONS	
Clear output aperture	23 mm
Divergence	Adjustable
Outer Diameter	30 mm
Mounting options	SM1 (male, female), ø30 mm
Transmission	>98%
LIDT	3 J/cm ² (10 ns @ 355nm)
	5 J/cm ² (10 ns @ 532 nm)
	10 J/cm ² (10 ns @ 1064 nm)

*Custom design available

Standard products

ITEM MODEL	EXPANSION	CLEAR INPUT APERTURE	RECOMMENDED MAX. INPUT BEAM SIZE, 1/e ²	CLEAR OUTPUT APERTURE	MECHANICAL LENGTH	WAVELENGTH	SKU
FEX-2	2 x	11.5 mm	ø7 mm	23 mm	65 mm	343-355 nm	7723
						515-532 nm	7725
						1030-1064 nm	7727
						1030-1064 + 515-532 nm	11149
FEX-3	3 x	11.5 mm	ø5.3 mm	23 mm	65 mm	343-355 nm	7725
						515-532 nm	7727
						1030-1064 nm	7729
						1030-1064 + 515-532 nm	11170
FEX-4	4 x	11.5 mm	ø4 mm	23 mm	90 mm	343-355 nm	7726
						515-532 nm	7727
						1030-1064 nm	11171
						1030-1064 + 515-532 nm	7741
FEX-5	5 x	11.5 mm	ø3.2 mm	23 mm	95 mm	343-355 nm	7742
						515-532 nm	7743
						1030-1064 nm	7744
						1030-1064 + 515-532 nm	11172
FEX-8	8 x	7 mm	ø2 mm	23 mm	104 mm	343-355 nm	7749
						515-532 nm	7750
						1030-1064 nm	7754
						1030-1064 + 515-532 nm	11173

Mounting accessories for fixed ratio beam expanders FEX


RECOMMENDED ACCESSORY	FOR BEAM HEIGHT OF	SKU
Adapter SM1 male to M20 X 1 male	-	9338
Adapter SM1 female to C-mount	-	9339
Adapter SM1 female to M20 X 1 male	-	9340
X-Y adjustable (3 adjusters) kinematic mount with post holder	50.8 mm (2")	9341
X-Y adjustable (3 adjusters) kinematic mount with post holder	76.2 - 100 mm (3" - 4")	9342



www.phototechnica.co.jp
フォトテクニカ株式会社

〒336-0017 埼玉県さいたま市南区南浦和 1-2-17
TEL: 048-871-0067 FAX: 048-871-0068
e-mail: voc@phototechnica.co.jp

Flat top converter FTC



Flat top converter unit is all in one motorised solution for a Gaussian beam transformation to a Flat-Top (Top Hat) beam. Any focusing element is needed. The beam profile remains Flat-Top shape along optical axis. The device consist of quartz wave-plate, space-variant wave-plate and a high contrast polariser. The FTC is produced in the UV, visible and NIR spectral ranges, from 250 nm to 2000 nm.

All optical components of the FTC are made for high LIDT and provide stable and reliable performance even using them with high power lasers in industrial applications. A secondary laser beam from Flat top converter unit can be rejected to an external beam dump. The beam dump is used for avoiding any thermal effects or stress in the housing of the FTC device.

Main features

- Quick change between Gaussian and Flat-top beam
- The beam profile remains Flat-Top shape along optical axis
- Integrated controller
- Designed according your laser specs.
- Clear aperture up to 15 mm
- Quick switching time - 0.2 sec
- High damage threshold up to 10J/cm² (10 ns @ 1064 nm)
- Conversion efficiency up to 70% (white on Flat-Top mode)

Application examples

- Precise laser micromachining
- Life sciences
- Research

Standard specifications

FLAT TOP CONVERTER FTC SPECIFICATIONS	
Input and output clear aperture	nds on waveplate
Conversion efficiency and transmission	Up to 70% (white on Flat-Top beam mode) No loss (black on Flat-Top Gaussian beam mode)
LIDT coating	>10 J/cm ² (10 ns @ 1064 nm)
Controller	USB and RS232
Control interface	External
Dimensions (H x W x L)	105 x 50 x 42.5 mm FTC 60 x 47 x 42.5 mm FTC with beam dump (BC-d)

*Custom design available

Standard products

MODEL	APERTURE	WAVELENGTH	ADJUSTMENT	TYPE	CONTROL INTERFACE	TYPICAL APPLICATION	SKU
FTC	ø 6 mm	1030 nm	Motorised	DDE	USB or RS232	Flat top converter	19750
	ø 6 mm	515 nm	Motorised	DDE	USB or RS232	Flat top converter	19751
	ø 3 mm	1030 nm	Motorised	DDE	USB or RS232	Flat top converter	19752
	ø 2 mm	515 nm	Motorised	DDE	USB or RS232	Flat top converter	19753
	ø 6 mm	1064 nm	Motorised	DDE	USB or RS232	Flat top converter	19754
	ø 3 mm	1064 nm	Motorised	DDE	USB or RS232	Flat top converter	19755
	ø 6 mm	532 nm	Motorised	DDE	USB or RS232	Flat top converter	19756
	ø 3 mm	532 nm	Motorised	DDE	USB or RS232	Flat top converter	19757



www.phototechnica.co.jp
フォトテクニカ株式会社

〒336-0017 埼玉県さいたま市南区南浦和 1-2-17
TEL: 048-871-0067 FAX: 048-871-0068
e-mail: voc@phototechnica.co.jp

Motorized polarization rotator MRO



Rotator (MRO) is a compact motorised device for laser polarisation control. The MRO is produced in the UV, visible and NIR spectral ranges, from 250 nm to 2000 nm. The device has external controller.

All optical components of the MRO are made for high LIDT and provide stable and reliable performance even using them with high power lasers in industrial applications.

Main features

- Compact design
- High resolution - 175543 μsteps in 360 deg rotation
- High accuracy - ±10 μsteps accuracy (± 0.02 deg)
- Clear aperture - 10 mm
- Fast adjustment - less than 0.2 sec (0 to 45 deg)

Application examples

- Flat top ir custom laser beam profile shaping
- Laser micromachining
- Biophotonics and microscopy

Standard specifications

SPECIFICATIONS	
Travel range	Y axis: 0 mm (±4 mm)
	Z axis: 4 mm (±2 mm)
Yaw: ±5.5 deg	Pitch: ±2.5 deg
	Resolution
Z axis: 10 μm/div	Yaw: 0.010 deg/div
	Pitch: 0.010 deg/div
Maximum load	Mounted horizontally: 1.5 kg
	Mounted vertically: 0.4 kg
Suitable optics	ø25.4 mm (1.0") x 3.8 mm thickness

Standard products

CLEAR APERTURE	CONTROL INTERFACE	WAVEPLATE	RETARDATION	LIDT	SKU
18 mm	USB or RS232	1064 nm	L/2	10 J/cm ² (10 ns@1064 nm)	19706
		1030 nm	L/2	10 J/cm ² (10 ns@1030 nm)	19707
		532 nm	L/2	5 J/cm ² (10 ns@532 nm)	19708
		515 nm	L/2	5 J/cm ² (10 ns@515 nm)	19709
		355 nm	L/2	3 J/cm ² (10 ns@355 nm)	19710
		343 nm	L/2	3 J/cm ² (10 ns@343 nm)	19701
		266 nm	L/2	2 J/cm ² (10 ns@266 nm)	19702
		257nm	L/2	2 J/cm ² (10 ns@257 nm)	19706
		1064 nm	L/A	10 J/cm ² (10 ns@1064 nm)	19708
		1030 nm	L/A	10 J/cm ² (10 ns@1030 nm)	19709
		532 nm	L/A	5 J/cm ² (10 ns@532 nm)	19709
		515 nm	L/A	5 J/cm ² (10 ns@515 nm)	19476
		355 nm	L/A	3 J/cm ² (10 ns@355 nm)	19527
		343 nm	L/A	3 J/cm ² (10 ns@343 nm)	19477
		266 nm	L/A	2 J/cm ² (10 ns@266 nm)	19711
		257nm	L/A	2 J/cm ² (10 ns@257 nm)	19710
without optics	None	None	None	19707	



www.phototechnica.co.jp
フォトテクニカ株式会社

〒336-0017 埼玉県さいたま市南区南浦和 1-2-17
TEL: 048-871-0067 FAX: 048-871-0068
e-mail: voc@phototechnica.co.jp