




UV-NIR laser beam visualizers


Main features

- Wavelength detection from UV to NIR
- Suitable for CW and pulsed laser light
- High sensitivity to laser radiation – 0,1 mW/mm²
- Damage threshold for pulsed laser – 1 J/cm², 10 ns
- Both sides are active

Application examples

- Laser alignment
- Research

Laser beam visualizers are designed to detect UV and IR both CW and pulsed laser light radiation. These visualizers are fabricated from aluminum with an organic polycrystal photosensitive region, which enables easy location of UV-VIS-NIR light beams and focal points. As it is not necessary to charge the active region both CW and pulsed laser light will be detected even in darkened room conditions.



Standard products

CLEAR APERTURE	ITEM MODEL	DETECTION SPECTRAL RANGE	EMISSION COLOR	THRESHOLD SENSITIVITY	SKU
29 mm	IRV-R-1	190-1090 + 1470-1600 nm	Red	0,01 W/cm ²	40462
	IRV-G-1	880-1070 nm	Green	0,02 W/cm ²	40463

**PHOTO
TECHNICA**

www.phototechnica.co.jp

フォトテクニカ株式会社

〒336-0017 埼玉県さいたま市南区南浦和 2-18-2

TEL:048-871-0067 FAX:048-871-0068

e-mail:voc@phototechnica.co.jp