

ORPHEUS | MIR



Broad-Bandwidth Mid-Infrared Optical Parametric Amplifier


FEATURES

- Broad-bandwidth MIR pulses at high repetition rate
- Continuously tunable in 2500 – 15000 nm range
- Short-pulse high-energy auxiliary output at 2000 nm
- Pumped by industrial-grade lasers for high stability
- CEP-stable option




ORPHEUS-MIR is an optical parametric amplifier (OPA) optimized for the efficient generation of broad-bandwidth MIR pulses. The laser system provides ultrashort pulses in the tuning range of 2.5 – 10 μm and reaches up to 15 μm with a narrow-bandwidth extension. Due to the novel system design, ORPHEUS-MIR provides < 100 fs pulses directly at the output. Signal and Idler outputs are available simultaneously. The system architecture is well-suited for high-energy and high-power PHAROS and CARBIDE femtosecond pump lasers. ORPHEUS-MIR serves as an excellent high-repetition-rate


source for spectroscopy, such as two-dimensional infrared (2D IR) and vibrational sum-frequency generation (SFG) spectroscopy. Combined with a narrow-bandwidth output of SHBC, it forms a compact laser system for SFG measurements, covering most of the MIR spectrum in a single shot and providing high spectral resolution. In addition, its high output stability is the key to fast and high-quality SFG imaging. Furthermore, for MIR applications requiring CEP-stable pulses, ORPHEUS-MIR provides unique CEP-stable option in the complete 2500 – 15000 nm range.




Typical tuning curves of **ORPHEUS-MIR**.
Pump: 80 W, 2 mJ, 40 kHz



Typical spectral bandwidth of **ORPHEUS-MIR**



Typical output spectrum (left) and pulse duration (right).
Measured at ≈ 3000 nm



Pulse-to-pulse energy stability of **ORPHEUS-MIR**.
Measured at ≈ 3000 nm

SPECIFICATIONS

Model	ORPHEUS-MIR
MAIN OUTPUT (2500 – 10000 nm)	
Tuning range	2500 – 4000 nm (Signal) 4000 – 10000 nm (Idler)
Maximum pump power	80 W
Pump pulse energy	200 μJ – 3 mJ
Pulse duration	< 100 fs
Conversion efficiency ¹⁾	> 1.2% @ 3000 nm > 1.0% @ 3500 nm > 0.6% @ 5000 nm > 0.3% @ 9000 nm
Spectral bandwidth ²⁾	> 300 cm ⁻¹ @ 2500 – 4000 nm > 200 cm ⁻¹ @ 4000 – 10000 nm
Long-term power stability, 8 h ³⁾	< 2% @ 5000 nm
Pulse-to-pulse energy stability, 1 min ³⁾	< 2% @ 5000 nm
AUXILIARY OUTPUT 1 (2000 nm)	
Output wavelength ⁴⁾	2000 ± 100 nm
Pulse duration	< 50 fs
Conversion efficiency ¹⁾	> 8%
Spectral bandwidth	> 350 cm ⁻¹
AUXILIARY OUTPUT 2 (1350 – 2000 nm)	
Tuning range ⁵⁾	1350 – 2000 nm
Pulse duration	< 300 fs
Conversion efficiency ¹⁾	Contact sales@lightcon.com
Spectral bandwidth	60 – 150 cm ⁻¹
WAVELENGTH EXTENSION (10000 – 15000 nm)	
Tuning range ⁶⁾	10000 – 15000 nm
Pulse duration	< 300 fs
Conversion efficiency ¹⁾	> 0.2% @ 12000 nm
Spectral bandwidth	100 – 200 cm ⁻¹

¹⁾ Specified as a percentage of pump power.


²⁾ FWHM (full width at half maximum).

³⁾ Expressed as NRMSD (normalized root mean squared deviation).


⁴⁾ Not tunable, optimized for best overall performance. Not simultaneous to OPA output.

⁵⁾ Simultaneous to OPA output. Available on request.

⁶⁾ Not available in collinear-output configuration.



DRAWINGS



ORPHEUS-MIR drawings